

# Upright Cooler

*The answer to all you'r display questions*



[www.fricool.com](http://www.fricool.com)

 [facebook.com/fricool-group](https://facebook.com/fricool-group)

# Upright Cooler

As Fricool is the best answer for all display solution, visi- cooler is the best way to cool your products and display them at the same time. visi- cooler are Plus Temperature Vertical Showcase Coolers which are used to store & display merchandising beverages, dairy, soft drinks, confectionary, juice, milk ... etc.,



- Low energy consumption
- Illuminated fluorescent light
- Uniform cooling by forced air circulation
- Clear product visibility with dual glass
- Self-closing door
- evaluated and approved under condition D
- Visi top Merchandiser
- Inner liner in pre-painted galvanized steel for long life and ease of maintenance.
- Certified Performance by International Laboratories
- a-Refrigerant R134

### Optional features

- Logo strips
- Lock
- Analog / digital thermometer
- Branding back panel stickers / silk screen
- Electric voltage protector stabilizer
- Gravity shelves
- Refrigerant CO2

Specifications		F - 12	F - 25	F - 40	F - 60	F - 120
NET CAPACITY	(LITRES)	120	285	420	640	1200
EXTERNAL DIMANTIONS	(MM)	D X W X H 510 X 500 X 900	D X W X H 600 X 600 X 1560	D X W X H 600 X 600 X 1950	D X W X H 710 X 700 X 2125	D X W X H 730 X 1296 X 2125
WEIGHT	(KGS)	54	88	105	134	204
INSULATION		CYCLOPENTANE				
DOOR LOCK		OPTION				
NO. OF SHELVES	(PCS)	3 ADJUSTABALE	4 ADJUSTABALE	5 ADJUSTABALE	6 ADJUSTABALE	10 ADJUSTABALE
CANOPY LIGHTING	(WATTS)	20				40
INTERNAL LIGHTING	(WATTS)	15	40		60	2 x 40
COMPRESSOR	(HP)	1/5	1/3	3/8	1/2	3/4
REFRIGERANT		R134-a				
EVAPORATOR FAN MOTOR	(WATTS)	1X5			2X5	3X5
CONDENSER FAN MOTOR	(WATTS)	1X5	1X10		1X16	
POWER SUPPLY		240-220V 50HZ.,240-220V 60HZ.				
TEMPERATURE CONTROL		MECHANICAL THERMOSTAT CONTROL				
DEFROST		OFF-CYCLE				
COOLING PERFORMANCE		3:7°C	0:6°C			
330ML CANS CAPACITY	FACING	6	7	8	8	8
	NO.OF CANS	108	245	350	560	1120
290ML BOTTLE CAPACITY	FACING	7	8	8	9	11
	NO.OF BOTTLE	49	192	240	360	1100
330ML Bottle CAPACITY	FACING	6	8	8	9	9
	NO.OF BOTTLE	36	192	240	360	720
500ml PET CAPACITY	FACING	6	7	8	8	8
	NO.OF BOTTLE	60	105	175	280	640
UNIT IN CONTAINER	20 FCL	88	39	27	24	12
	40 FCL	167	83	57	45	27
SAFETY CERTIFICATION		CE, SASO, ISO 18001, 14001, 9001				

( Option List ( Order Before Order

Hanging Shelf - Voltage Stabilizer - Voltage Protector - Bottle opener