



• Blood Lines for Haemodialysis

- High quality components including self-ejecting patient connectors and latex-free injection ports.
- PVC tubing is designed to withstand conditions of manipulation with high accuracy and consistency of blood flow.
- Assured product safety by permanent in-process control and 100% inspection for leakage.
- Laboratory tests demonstrated an accurate and consistent flow rate over time and excellent performance under extreme conditions.
- A wide range of different configurations are available to suit all dialysis machines.

• AV Fistula Needles for Haemodialysis

- Ensured maximum blood flow with minimum resistance by a non-traumatic siliconized ultra-thin needle wall.
- Better blood flow is also provided by a side hole (Back-Eye).
- Easy painless penetration is guaranteed by optimum inclination of the cutting edge.
- Available sizes: 14G - 15G - 16G - 17G..

• Drainage Bags for Haemodialysis

- Providing a closed system to reduce the infection risk.
- Specifications regarding the film type and welding technology are considering both clinical efficiency and cost effectiveness.
- A large range of standard bag configurations and accessories are available with the flexibility to be further customized to introduce the most suitable product.
- Drainage bags can be used for other applications such as bags for peritoneal dialysis or bags for parenteral nutrition.

Head Office: 13, Obour Buildings, Salah Salem St., Cairo, Egypt
P.O. Box 215 Heliopolis, Cairo
Factory: 10th of Ramadan City - Industrial Area C3, Egypt
Tel: +2015 361 684 Fax: +2015 364 104
E-mail: info@afrimedical.com export@afrimedical.com
Web Site: www.afrimedical.com

Dialysis Products



Afri Medical as a pioneer company in the medical device disposables manufacturing, has introduced the best quality products to meet the needs of Dialysis Market with high efficiency and reliability.

All products are based on raw material with the highest medical qualities, manufacturing process is complying with the most recent international standards and strict quality control inspections to insure product safety, high biocompatibility, excellent stability and performance.

• Venaflor PolyEtherSulfone Dialyzer

- Venaflor PolyEtherSulfone Dialyzer is an advanced haemodialysis capillary dialyzer manufactured by Afri Medical and complying with the international standards to introduce a superior dialyzer with high efficiency and optimum cost.
- Venaflor PolyEtherSulfone Dialyzer has been designed for use in haemodialysis and associated forms treatment for chronic or acute kidney failure patients.

• Chemical and Physical Properties

- Venaflor PolyEtherSulfone Dialyzer is based on a fully synthetic dialysis membrane made of PolyEtherSulfone and combined in a particular way with spacer yams consist of multifilament threads integrated into the fiber bundles.
- This combination improves dialysate distribution throughout the dialyzer to increases clearance values and maintains consistent performance.

Membrane	PolyEtherSulfone
Housing and Ports	Polycarbonate
Potting Resin	Polyurethane
O-Rings	Silicon
Protective Caps	Polypropylene

• Performance Characteristics

Specifications	Model (Medium Flux Gamma)						Tolerance
	V.P. 100	V.P. 130	V.P. 150	V.P. 170	V.P. 190	V.P. 210	
Surface Area(m ²)	1.0	1.3	1.5	1.7	1.9	2.1	
Wall Thickness(m)	35	35	35	35	35	35	±5%
Inner Diameter(m)	200	200	200	200	200	200	±15%
Performance							
Urea (ml/min)	194	221	225	245	250	285	±10%
Cratinine (ml/min)	184	198	217	222	224	233	±10%
Phosphate (ml/min)	115	130	145	175	159	163	±10%
Vitamin B12 (ml/min)	57	74	115	119	120	122	±10%
UFRH ₂ O (ml/hr.mmHg)	30	38	43	45	58	60	±20%

Specifications	Model (Medium Flux EtO)						Tolerance
	V.P. 100	V.P. 130	V.P. 150	V.P. 170	V.P. 190	V.P. 210	
Surface Area(m ²)	1.0	1.3	1.5	1.7	1.9	2.1	
Wall Thickness(m)	35	35	35	35	35	35	±5%
Inner Diameter(m)	200	200	200	200	200	200	±15%
Performance							
Urea (ml/min)	194	221	225	245	250	285	±10%
Cratinine (ml/min)	184	198	217	222	224	233	±10%
Phosphate (ml/min)	115	130	145	175	159	163	±10%
Vitamin B12 (ml/min)	57	74	115	119	120	122	±10%
UFRH ₂ O (ml/hr.mmHg)	8.6	10.4	11.9	14	16	17	±20%

-Q_d=300 ml/min., Q_d=500 ml/min. With physiological NaCl Solution 0.9% at 37± 0.5 °C. Q_d=10
* In Vitro.

- Venaflor PolyEtherSulfone Dialyzers provide for low and middle molecules a high clearance, stable over time with low protein adsorption yielding an efficient dialysis.

• Advantages

- PolyEtherSulfone membrane exhibits excellent performance that provide dialyzers with many advantages which can be summarized as follows:



• Very High Performance

- Venaflor PolyEtherSulfone Dialyzer has a very high Permeability for all relevant uremic toxins due to its typical unique structure and proper wall thickness.

- Venaflor PolyEtherSulfone Dialyzer represents an optimized synthetic low-flux dialyzer since it combines favorable high-flux features, i.e. middle molecule removal, with the advantages of low-flux dialyzer, i.e. less prone to pyrogen transfer from dialysate.

• Excellent Biocompatibility

- Venaflor PolyEtherSulfone Dialyzer has a very good Biocompatibility profile causing low activation of the complement system, low activation of white blood cells and platelet content, and low thrombogenicity.

• Sterilizable with all methods

- Due to its high chemical and physical stability, Venaflor PolyEtherSulfone Dialyzers can be sterilized with all available sterilization methods. (EtO, Gamma and Steam)

* High flux dialyzers available upon request.

